



Note: The model in the photo is Model-CPS-B with optional 3 Tray Module.



Apeos™

Embark on your digital transformation journey

Designed to accelerate your digital transformation (DX) journey, new Apeos series with its smart and seamless integration features present itself as a trusted digital partner.









True scalable solutions to start your digital journey



Note: The model in the photo is Model-CPS-B with optional 3 Tray Module.

Apeos 3561 / 3061 / 2561

Designing Simplicity

Designed for all, our devices deliver ease of use, accessibility and personalisation features for a true intuitive experience.

Offering Scalability

Promote easier collaboration and enhanced accessibility with paperless office solutions.

Creating Environmental Sensitivity

Driving organisation awareness towards creating a low impact environment with advanced features such as low melting point (low energy) toner technology, smart power-saving feature or staple-free finishing.







Designing simplicity for everyday business needs

Easy-to-use 7-inch control panel delivers intuitive user experience and personalisation

The control panel serves as the gateway, connecting you to various smart applications on the multifunction printer at the touch of your finger. The touch panel provides excellent visibility and operability, responding to every touch and swipe for effortless navigation.



- *1: Connect to the machine via wireless environment or Wi-Fi Direct® connection. It can be downloaded free of charge from Google Play™ or App Store.
- *2: Copy, fax, print or scan.
- Note: AirPrint, Mopria® Print Service, and Mopria Scan are supported for printing or scanning by using a mobile device.

Pleasant, gentle lighting notifies you of operation completion or errors

Note: The displayed screen differs from the factory default. Additionally, the LED lighting status varies depending on the situation. The LED lighting status in the image is for illustrative purposes only.

Quickly access frequently used settings

On the Pins screen, you can restart jobs from the job history. Frequently used settings can be "pinned" to save time.

User-friendly home screen

Frequently used app buttons can be arranged and customised based on individual user's preference.



Remote Operation Panel

Device administrators can set up and manage the multifunction printer remotely. By launching the Remote Operation Panel from a web browser, the multifunction printer's control panel can be displayed to and operated from a PC.

Note: Within the same intranet. While the Remote Operation Panel is active, the multifunction printer's control panel cannot be operated. Additionally, the Remote Operation Panel cannot be launched while the user is operating the multifunction printer.

Make an impression with every print

High-resolution printing of 1,200 x 2,400 dpi is achieved with newly adopted LED printhead. The newly developed toner, combined with advanced image enhancement processing, reproduces diagonal lines, character outlines, and smooth halftones, giving every print a professional finish.

Small footprint fits in every office space

The compact design with width of 577 mm and depth of 659 mm* fits everywhere, including tight spaces, maximising office space utilisation.

* For 1 Tray standard configuration.

Print seamlessly with versatile media support

Supports wide range of paper size and weight*1, giving you the flexibility to personalise and print on envelope*2 direct mail, flyers, or even long banners*3.

- $^{\rm *1:}$ Paper weight from 52 to 300 gsm. 106 to 300 gsm, when the Envelope Feeder is on. $^{\rm *2:}$ Envelope and postcard can be printed directly from Tray 1.
- *3: Long sheets up to 297 x 1,200 mm





Professional finishing solutions (optional) that scale with business needs Finisher-A3 Finisher-B4 / B5*1 Supports single and double Staple-free Stapling*2 + Side Tray + Booklet Maker Unit Supports output from three locations for Copy, Fax, and Print functions. This way, important received faxes are ·Staple + Side Tray not missed, and output paper can be quickly retrieved 3 Way Staple • Staple-free Staple*2 • Punch*3 output ·Saddle Staple*4 ·Single Fold* *1: Optional 3 Tray Module or 1 Tray Module with Cabinet and KIT Finisher-B4/B5 INST are required. *2: Staple-free stapling is available with Finisher-B5. *3: Optional Punch Module is required. *4: Booklet Maker Unit is required. When specifying Saddle Staple or Single Fold with Finisher-B4/B5, paper is not folded but creased. *5: 80 gsm paper or less.

Promotes DX and collaboration with paperless office solutions

Quick digitisation of high-volume originals

1 pass, 2-sided colour scanning of up to 80 ppm*1

The high-speed 1-pass, 2-sided scanning Automatic Document Feeder holds up to 130 sheets*2 and scans 2-sided document in one go, allowing you to digitise large documents swiftly and effortlessly.

Note: Installed for Model-CPS-B as standard. *1: Our Standard Document (A4 LEF), 200 dpi, to Folder.

- *2: 70 gsm paper.
- Supports scanning of smallsized documents (49 x 85 mm), thick cheques and thin paper receipts (38 to 128 gsm).

Note: Custom Sizes from 49 x 85 mm to 55 x 91 mm are available from 38 to 209 gsm.


- Scanned documents can be transferred to e-mail, PC, or shared servers.
- Supports multi-sending, such as saving a copy to your PC while sending an e-mail to a client in a single scan.
- Scan directly to / print directly from a standard USB 2.0 flash drive for greater work efficiency.



The large grip width makes it easier to lift the automatic document feeder.



Automatically scans small originals as-is to a standard size



Digitisation of paper documents for effortless document management


Scan Delivery Light* reduces your scanning workload by simplifying complicated and repetitive scanning workflow.

Standard rules and templates can be created easily, allowing you to complete multiple actions (scan settings, storage destination designation and file renaming) with a single touch.

Scanned information can also be managed and utilised centrally, improving productivity and resource optimisation.

* Optional.

Scan Delivery Light



Copying and scanning ID Cards

You can copy both sides of an ID card on a single sheet of paper, or scan and transfer to SMB / FTP / SFTP / Email / URL / My Folder, allowing for easy access and printing when needed.







Serverless solutions for smarter business operations

Our multifunction printer supports serverless solutions, helping you reduce operational costs and improve efficiency without the need for additional hardware investment such as server.

- Serverless Authentication* integration manages and shares user authentication information securely between multiple printers without the need of a server.
- Serverless On-Demand Print* manages and connects multiple devices, having the flexibility to print and collect the printouts from any of the connected devices.

*Optional


Seamless integration of multifunction printer and cloud storage

By linking FUJIFILM IWpro* on the multifunction printer with cloud storage, digitised documents can be utilised easily. You can automate the process of assigning folder and file names to scanned or received fax documents, and storing them in a designated location, including the cloud storage. Documents can be previewed directly from the operation panel of the multifunction printer before printing. Seamless printing environment can be achieved without the need for a PC.

Print securely, anywhere, from any device

Documents uploaded to FUJIFILM IWpro can be securely output from remote office locations, enabling hybrid work styles for greater flexibility.

* FUJIFILM IWpro is a cloud service provided by FUJIFILM Business Innovation. A separate contract is required for this service.



The multifunction printers of the future

FUJIFILM Business Innovation aims to address environmental issues through climate change mitigation and resource circulation efforts in our business activities. Our products are developed with various innovations and technologies that balance environmental impact reduction and usability.

New toner and a fusing unit with low fusing temperature and high image quality

Toner fusing is the most energy-intensive process in a multifunction printer. To reduce power consumption, we are introducing new technologies in our toner and fusing unit.

Our new toner features functional resin and small particle technology, enabling fusing at an industry-leading low temperature*1. Together with the new fusing unit, the Apeos 3561 series achieves a fusing temperature that is 22 degrees lower than the previous model*2.

This breakthrough reduces environmental impact while maintaining exceptional image quality, delivering sharp text, precise lines and smooth gradation.

- *1: The toner fusing temperature for A3 laser multifunction printers based on internal study conducted in May 2025.
- *2: Apeos 3560 series.

Designed for now and for the future

In the effort to promote recycling of resources, recycled plastic materials are used* for parts such as the front cover and trays. We have overcome challenges to devise ways to suppress uneven colour of the appearance of recycled plastic, which is said to be difficult to mold. And by improving the strength and rigidity of the parts, we ensure the quality of the product.

Furthermore, our products have been redesigned to allow easy disassembly and cleaning, making them easy to reuse and recycle in the future.

 * In the case of 4 Tray configuration with Duplex Automatic Document Feeder. 15 % of the total plastic weight of the device is recycled material.

Technologies for energy conservation

- Less energy and compact with high resolution printing on LED printhead.
- Saves energy with quick startup and smart power saving feature that solely powers on the required parts according to the functions being used by users.



Safeguarding your DX journey with market-leading security

As network connected information devices, the multifunction printer is equipped with state-of-the-art security features to protect your valuable information assets from cyber-attacks and rapidly evolving security threats.

Protect from unauthorised user

- Unauthorised operations and access are prevented by user authentication and usage restrictions.
- Expansion with Secondary Ethernet* allows a single multifunction printer to be used on a separated network, etc.
- * Optional

Protects Data

- Encryption of communication paths with TLS and IPsec
- Protection of scanned files and e-mails through encryption/electronic signatures
- Data writing to SSD is encrypted with robust AES-256 encryption, etc.

Protect from unauthorised access

- Account lock function
- Restriction of accessible IP addresses
- Prevention of software tampering during multifunction printer startup and operation
- Automatic repair function upon detection of tampering at startup, etc.

Prevent information leaks due to operational errors

- Fixing the delivery destination of scanned documents
- Double input of fax destinations, etc.

Reliable support system

Easy solutions to resolve problems

From supplies replacement to unexpected device failures, most problems can be resolved without waiting for the service representatives or sales representatives.

1. Resolve problem using the "Help" function on the device

- Self Help information is available on the control panel
- Self Help information can be accessed via the mobile device by scanning the QR code displayed on the control panel

2. "Remote Assistance" with the help of operators

- Connects directly to the Support Centre
- An operator will remotely access the multifunction device to resolve the problem by guiding through the steps on the shared control panel

Device Setup Editor

Device Setup Editor is a service that always backs up the latest setting information to a cloud server. It allows you to be prepared for unexpected situations and use your multifunction printer with confidence.

Note: You need to apply for using the Device Setup Editor. (free of charge)

Keeping a close eye on your multifunction device on a daily basis

Connecting your multifunction printer to our EP service* via the internet allows for checking of billing meter, automatic delivery of consumables when cartridges level is low, daily status monitoring, and machine error detection for early intervention to rectify problem. This minimises operation downtime and reduces administrator's burden.

Note: The content of the services provided may vary depending on the usage region. For details, please contact one of our sales representative.

* You need to apply for using the EP service. (free of charge)

Apeos 3561 / 3061 / 2561 Functions & Specifications

Basic Specifications / Copy Function

Item		3561	3061	2561	
Туре		Desktop / Console			
Memory Capacity		4 GB (Max: 4 GB)			
Storage Device Capacity*1		256 GB			
Scan Resolution		600 x 600 dpi			
Printing Resolution		1,200 x 2,400 dpi			
			ins / Custom Services] *3		
Warm-up		When enabled: 26	seconds or less (23 degi	rees Celsius room temperature) rees Celsius room temperature)	
Recovery (Recovery Sleep Mod	Time from	13.6 seconds or le (23 degrees Celsiu	ss us room temperature)	11.0 seconds or less (23 degrees Celsius room temperature)	
Original Si		Maximum of A3. 1	1 x 17". 297 x 432 mm fc		
	Tray 1*4	Maximum of A3, 11 x 17", 297 x 432 mm for both Sheet and Book Max: A3, 11 x 17", Min: A5 SEF, Envelope*5, Postcard (100 x 148 mm) Custom Size: 90 x 98 mm to 297 x 432 mm			
Paper	Tray 2, 3, 4	Max: A3, 11 x 17"			
Size	Bypass Tray		; Min: A5 SEF, Envelope* 98 mm to 297 x 432 mm	⁶ , Postcard (100 x 148 mm) า	
	Image loss width*7	Lead edge 4.0 mm	n, Trail edge 2.0 mm, Righ	t / Left edge 2.0 mm	
Paper	Paper Tray	52 to 300 gsm			
Weight*8*9	Bypass Tray	52 to 300 gsm			
First Copy (Output Time	4.6 sec. (A4 LEF)		5.9 sec. (A4 LEF)	
	A4 LEF / JIS B5 LEF	35 ppm	30 ppm	25 ppm	
Continuous	A4	26 ppm	23 ppm	19 ppm	
Copy Speed*10	JIS B5	20 ppm	17 ppm	14 ppm	
Speeu	JIS B4	22 ppm	20 ppm	16 ppm	
	A3	19 ppm	17 ppm	14 ppm	
	Standard	520 sheets x 1-tra	y + Bypass Tray 96 sheet		
Paper Tray Capacity*11	Optional	1 Tray Module / 1 Tray Module with Cabinet: 520 sheets x 1-tray 3 Tray Module: 520 sheets x 3-tray			
	Max	2,176 sheets [Standard + 3 Tray Module]			
Output Tray Power Sup		Upper Center: 250 sheets (A4 LEF), Lower Center: 250 sheets (A4 LEF) AC220-240 V +/- 10 %, 8 A, 50/60 Hz common			
Maximum Power Consumption		1.76 kW (AC220 V +/- Sleep Mode: 0.3 V Low Power Mode:	10 %), 1.92 kW (AC240 V +/- 10 %) V (AC230 V +/- 10 %) 40 W (AC230 V +/- 10 %) V (AC230 V +/- 10 %)	1.76 kW (AC220 V +/- 10 %), 1.92 kW (AC240 V +/- 10 %) Sleep Mode: 0.3 W	
Dimensions		<code>Model-CPS:</code> W 577 x D 659 x H 769 mm W 577 x D 659 x H 872 mm (when optional 1 Tray Module is installed.) W S87 x D 659 x H 1,120 mm (when optional 1 Tray Module with Cabinet is installed.) W S87 x D 659 x H 1,120 mm (when optional 3 Tray Module is installed.) W S87 x D 659 x H 1,120 mm (when optional 3 Tray Module is installed.) Model-CPS-B: W 577 x D 659 x H 775 mm W 577 x D 659 x H 878 mm (when optional 1 Tray Module is installed.) W S87 x D 659 x H 1,126 mm (when optional 1 Tray Module with Cabinet is installed.) W S87 x D 659 x H 1,126 mm (when optional 3 Tray Module is installed.)			
Weight*13		Model-CPS: 57 kg 74 kg (when optional 1 Tray Module is installed.) 80 kg (when optional 1 Tray Module with Cabinet is installed.) 82 kg (when optional 3 Tray Module is installed.) Model-CPS-8: 58 kg 75 kg (when optional 1 Tray Module is installed.) 81 kg (when optional 1 Tray Module with Cabinet is installed.) 83 kg (when optional 3 Tray Module is installed.)			

*1: Storage Device Capacity is not totally available for customers. *2: It may change depending on usage conditions. *3: Embedded Plug-ins / Custom Services are enabled as factory default. *4: 90 x 98 mm to 241 x 372 mm is available when the Envelope Feeder is on. *5: Supported standard envelope sizes are Commercial#10, Monarch 7 3/4, DL, ISO-C4, etc. *6: Supported standard envelope sizes are ISO-C4 and ISO-C5. *7: Up to A3 size. *8: It is recommended to use our recommended paper. Correct print output may not be possible depending on the requirement. *9: 106 to 300 gsm, when the Envelope Feeder is on. *10: The speed may be reduced due to the image quality adjustment. *11: 80 gsm paper. *12: 70 gsm paper. *13: Excluding Toner Cartridge.

Print Function

ltem		Description	
Туре		Built-in type	
	Tray 1	Same as the Basic Specifications / Copy Function	
Print Size	Tray 2, 3, 4	Same as the Basic Specifications / Copy Function	
	Bypass Tray	Max: A3, 11 x 17"; Min: A5 SEF, Envelope*1, Postcard (100 x 148 mm) Custom Size: 89 x 98 mm to 297 x 1,200 mm*2	
	Image loss width*3	Lead edge 4.0 mm, Trail edge 2.0 mm, Right / Left edge 2.0 mm	
Continuou Speed*4	ıs Print	Same as the Basic Specifications / Copy Function	
Printing	Standard	[PCL Driver] Standard: 1,200 x 2,400 dpi, High Quality: 1,200 x 2,400 dpi, High Resolution: 1,200 x 1,200 dpi	
Resolution	Optional	[Adobe® PostScript® 3™ Driver] High Speed (Standard): 600 x 600 dpi, High Quality: 1,200 x 2,400 dpi, High Resolution: 1,200 x 1,200 dpi	
Page	Standard	PCL5 / PCL6	
Description Language	Optional	Adobe® PostScript® 3™	
Supported Operating System*5	Standard	[PCL Driver] Windows 11 (64 bit), Windows 10 (32/64 bit), Windows Server 2025 (64 bit), Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) [Mac OS X Driver] macOS 15 / 14 / 13 / 12 / 11	
	Optional	[Adobe® PostScript® 3™ Driver] Windows 11 (64 bit), Windows 10 (32/64 bit), Windows Server 2025 (64 bit), Windows Server 2022 (64 bit), Windows Server 2019 (64 bit), Windows Server 2016 (64 bit) macOS 15 / 14 / 13 / 12 / 11	
Interface	Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T, USB3.0	
interrace	Optional	Wireless LAN (IEEE 802.11a / b / g / n / ac)	

*1: Supported standard envelope sizes are Commercial#10, Monarch 7 3/4, DL, ISO-C4, etc. *2: Long paper of 106 to 220 gsm (Extra Heavyweight) is available. The printed papers are delivered to the Side Tray when Finisher-A3 is attached. *3: Up to A3 size. *4: The speed may be reduced due to the image quality adjustment. The printing speed may be reduced depending on the document. *5: Please refer to our official website for the latest supported OS.

Scan Function

Item		Description	
Туре		Colour Scanner	
Scan Resolution		600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi	
Scan Speed		Same as the Scan Speed for the Duplex Automatic Document Feeder	
1-46	Standard	Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T	
Interface	Optional	Wireless LAN (IEEE 802.11a / b / g / n / ac)	

Fax Function (Optional)

, , ,	•		
Item	Description		
Original Size	Max: A3, 11 x 17", Long document (Longest 600 mm*1)		
Recording Paper Size	Max: A3, 11 x 17"; Min: A5		
Transmission Time	2 seconds and more but fewer than 3 seconds*2		
Transmission Mode	ITU-T G3		
Applicable Lines	Telephone subscriber line, PBX, Fax communication (PSTN), Maximum 3 ports*3 (G3-3 ports)		

*1: When Duplex Automatic Document Feeder is used. *2: When A4 size document with approximately 700 characters is transmitted in standard image-quality (8 x 3.85 lines/mm) and in high-speed mode (28.8 kbps or faster, JBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the contents of the document, the type of machine receiving the fax, and line condition. *3: No. of FAX lines is up to 3 ports. Port refers to number of channels for FAX.

Duplex Automatic Document Feeder B1-C

Item		3561	3061	2561	
Original Size*1/		Max: A3, 11 x 17"; Min: A6			
Paper Weight		38 to 128 gsm (In Duplex: 50 to 128 gsm)			
Capacity*2		110 sheets			
Scan	Copy (A4 LEF, Simplex)	35 ppm	30 ppm	25 ppm	
Speed*3	Scan	B/W: 55 ppm, Colour: 55 ppm [Standard Document (A4 LEF), 200 dpi, to Folder]			

Note: Installed for Model-CPS as standard. *1: Custom Size is 125×85 mm to 297×432 mm. *2: 70 gsm paper. *3: The scanning speed varies depending on the documents.

Duplex Automatic Document Feeder B4-PC

Item		3561	3061	2561	
Original Size*1 / Paper Weight		Max: A3, 11 x 17"; Min: A6 38 to 128 gsm (In Duplex: 50 to 128 gsm) *2			
Capacity*3		130 sheets			
C	Copy (A4 LEF, Simplex)	35 ppm	30 ppm	25 ppm	
Scan Speed* ⁴	Scan	B/W: 80 ppm, Colour: 80 ppm (1 pass, 2 sided scanning: B/W 80 ppm, Colour 80 ppm) [Standard Document (A4 LFF), 200 dpi, to Folder]			

Note: Installed for Model-CPS-B as standard. *1: Custom Size is 49×85 mm to 297×432 mm. *2: Custom Sizes from 49×85 mm to 55×91 mm are available from 38 to 209 gsm. *3: 70 gsm paper. *4: The scanning speed varies depending on the documents.

Side Tray (Optional)

Item	Description
Paper Capacity*	100 sheets
Dimensions / Weight	W 328 x D 540 x H 198 mm, 3 kg

^{* 70} gsm paper.

Notes

- If the storage media of the base unit fail, loss of received data, accumulated data, registered setting data, etc. may occur. In no event shall "the company" be liable for any damages whatsoever arising from loss of data.
- Functional spare parts will be available for at least 7 years after the product is no longer manufactured.

Finisher-A3 (Optional)

Thistier 7.5 (optional)				
Item		Description		
Туре	Center Tray	Stack		
	Finishing Tray	Sort (Offset available*1*2) / Stack (Offset available*1*2)		
D	Center Tray	A4, A3		
Paper Size	Finishing Tray	Max: A3, 11 x 17"; Min: A6, Postcard (100 x 148 mm) Custom Size: 89 x 98 mm to 297 x 432 mm		
Paper	Center Tray	52 to 300 gsm		
Weight	Finishing Tray	52 to 256 gsm		
	Center Tray	A4 LEF: 125 sheets A4 SEF, A3: 50 sheets		
Paper Capacity* ³	Finishing Tray	[Without Stapling] A4 LEF: 500 sheets, JIS B4: 250 sheets, A3 or larger: 200 sheets, Mixed Size Stacking**: 250 sheets (With Stapling) A4 LEF: 30 sets or 500 sheets, JIS B4: 250 sheets, A3 or larger: 200 sheets, Mixed Size Stacking**: 250 sheets		
	Capacity	A4: 50 sheets (90 gsm or less), JIS B4 or larger: 30 sheets (90 gsm or less)		
Staple	Paper Size	Max: A3, 11 x 17"; Min: JIS B5 LEF Custom Size: 203 x 182 mm to 297 x 432 mm		
	Paper Weight	52 to 256 gsm		
	Position	Single stapling, Dual stapling		
Dimensions / Weight		W 465 x D 484 x H 248 mm, 11 kg		

*1: [No Offset] is selected by factory default. *2: Outputs less than 190 mm width are delivered without offset stacking. *3: 70 gsm paper. *4: When larger size sheets are stacked on top of smaller size sheets: 250 sheets (when large size sheets are smaller than A3) / 200 sheets (when large size sheets are A3 or larger). The same applies to when staple-free and stapled bindings are mixed or different stapling positions are


Finisher-B4 / B5 (Optional)

	2., 20	(Optional)			
Item		Finisher-B4	Finisher-B5		
Туре	Center Tray	Stack			
	Finishing Tray	Sort (Offset available*1*2) / Stack (Offset available*1*2)			
Paper	Center Tray	Max: A3, 11 x 17"; Min: A5; Custom Si	ze: 148 x 148 mm to 297 x 432 mm		
Size*3	Finishing Tray	Max: A3, 11 x 17"; Min: A5; Custom Si.	ze: 148 x 148 mm to 297 x 432 mm		
Paper	Center Tray	52 to 300 gsm	52 to 300 gsm		
Weight*4	Finishing Tray	52 to 300 gsm			
	Center Tray	200 sheets (80 gsm or less)			
Paper Capacity* ⁵	Finishing Tray	[Without Stapling] A4: 2,000 sheets, JIS B4 or larger: 1,000 sheets, Mixed Size Stacking*6: 300 sheets [With Stapling] A4: 100 sets or 1,000 sheets*7, JIS B4 or larger: 75 sets or 750 sheets [With Booklet Finishing*8] 50 sets or 600 sheets [With Fold*8] 500 sheets			
	Capacity	50 sheets (90 gsm or less)	Staple: 50 sheets (90 gsm or less) Staple-free Staple*9*10: 10 sheets (80 gsm or less)		
Staple	Paper Size	Max: A3, 11 x 17"; Min: A5 LEF Custom Size: 210 x 148 mm to 297 x 432 mm			
	Paper Weight	52 to 256 gsm	Staple: 52 to 256 gsm Staple-free Staple*9*10: 64 to 105 gsm		
	Position	Single stapling, Dual stapling			
	Paper Size*12	Max: A3, 11 x 17"; Min: A5 LEF Custom Size: 210 x 148 mm to 297 x 4	32 mm		
Punch*11	Paper Weight	52 to 220 gsm			
	Number of Holes	2-hole / 4-hole punch or 2-hole / 3-hol	e punch (US Specifications)		
Booklet	Paper Size	Max: A3, 11 x 17"; Min: A4, Letter Custom Size: 210 x 279 mm to 297 x 432 mm			
Finishing*8	Capacity	Saddle Staple: 15 sheets, Single Fold: 5 sheets			
	Paper Weight	Saddle Staple: 64 to 80 gsm*13, Single Fold: 64 to 105 gsm			
		W 618 x D 653 x H 1,047 mm With Booklet Maker Unit: W 618 x D 67	73 x H 1,076 mm		
Weight		26 kg Punch Module: + 2 kg, Booklet Maker Unit: + 10 kg	28 kg Punch Module: + 2 kg, Booklet Maker Unit: + 10 kg		

Booklet Maker Unit: + 10 kg

Note: Finisher-B4 / Finisher-B5 is available only when optional 1 Tray Module with Cabinet or 3 Tray Module is attached to Main Unit. Note: Only stapled stapling is available with Finisher-B4. You cannot add staple-free stapling function. Note: Both stapled stapling and staple-free stapling are available with Finisher-B5. Note: Kit Finisher-B4/B5 INST is required.

*1: The offset feature is set to disabled by factory default. *2: Outputs whose weight is 257 gsm and more or width is less than 210 mm are delivered without offset stacking. *3: Paper in the sizes larger than A3 or 11 x 17" or smaller than A5 are delivered to the Centre Tray. *4: Documents may not be printed correctly depending on usage conditions. (52 to 55 gsm, 257 gsm and more) *5: 70 gsm paper. *6: When larger size sheets are stacked on top of smaller size sheets. *7: 75 sets or 750 sheets with dual stapling. *8: The Booklet Finishing function requires the optional Booklet Maker Unit for Finisher-B. Make a crease allows you to fold easily. After a job with the Booklet Finishing function specified has been output, the next job may not be delivered until the sheets are removed from the output tray. Also, if larger size sheets are stacked on top of smaller size sheets after a job with the Booklet Finishing function specified has been run, the next job may not be delivered until the sheets are removed from the output tray. *9: Staple-free stapling is available with Finisher-B.* *10: Staple-free stapling does not have binding force equal to stapled splang. Bound part may be easily separated depending on the paper, temperature, humidity, and how the page is turned over. *11: The Punch function requires the optional 2/4 Hole Punch Module for Finisher-B or US 2/3 Hole Punch Module for Finisher-B or US 2/3 Hole Punch Module for Finisher-B or US 2/3 Hole P



FUJ!FILM

FUJIFILM Business Innovation Vietnam Co., Ltd.

Head Office

Ground Floor, 2nd Floor and 19th Floor, The Hallmark Building, 15 Tran Bach Dang, An Khanh Ward, Hochiminh City Tel: (84-28) 3829 0038 Fax: (84-28) 3829 0032

Hanoi Branch & Showroom

T4th Floor, VCCI Tower, 9 Dao Duy Anh, Kim Lien Ward, Ha Noi Tel: (84-24) 3824 1063 Fax: (84-24) 3824 1113

Haiphong Branch

Room 515, 5th Floor, TD Business Center, 20A Le Hong Phong St., Gia Vien Ward, Hai Phong 12 Tran Phu, Ngo Quyen Dist., Hai Phong Tel: (84-255) 3859 236 Fax: (84-255) 3859 239

Danang Branch

rd Floor, Danabook Tower, No. 76-78 Bach Dang Street, Hai Chau Ward, Da Nang Tel: (84-236) 3892 896 Fax: (84-236) 3892 895

FUJIFILM Business Innovation aims to address environmental issues through climate change mitigation and resource circulation efforts.

The available model varies depending on the country/region. Please ask the sales representatives for details.

The product specifications, appearance and other details in this brochure are subject to change without

Reproduction Prohibitions Please note that reproduction of the following is prohibited by law: •Domestic and foreign currencies, government-issued securities, and national bonds and local bond certificates.
•Unused postage stamps, post cards, etc. •Certificate stamps stipulated by law. •Reproducing works forming the subject matter of copyright (literary works, musical works, paintings, engravings, maps, cinematographic works, drawings, photographic works, etc.) is not permitted unless the reproduction is for the purpose of personal use, family use or other similar uses within a limited circle.

Trademarks • FUJIFILM, FUJIFILM logo and FUJIFILM IWpro are registered trademarks or trademarks of

Apeos, DocuWorks and Working Folder are registered trademarks or trademarks of FUJIFILM Business

Innovation Corp.

-Microsoft, Active Directory, Azure, Microsoft Entra, Microsoft Edge, Excel, OneDrive, PowerPoint, SharePoint,
-Microsoft Teams, Windows, and Windows Server are registered trademarks of US Microsoft Corporation in the U.S.
and other countries. -Apple, Mac, macOS, OS X, AirPint, and AirPint logo are trademarks of Apple Inc. registered in
the U.S. and other countries and regions. -Adobe, Adobe logo, PostScript, and PostScript logo are either registered trademarks or trademarks of Abobe in the United States and/or other countries. -Mopria, the Mopria Logo, and
the Mopria Alliance word mark and logo are registered and/or unregistered trademarks and service marks of
Mopria Alliance, Inc. in the United States and other countries. -QR Code is a registered trademark of DENSO WAVE
INCORPORATED. -All product names and company names mentioned in this brochure are trademarks or registered
trademarks of their respective companies.



For Your Safety

Before using the product, read the Instruction Manual carefully for proper use. Use the product with the power source and voltage specified. Be sure to establish ground connection. Otherwise, electronic shock may result in the case of a failure or short circuit.