

Revoria Press SC285S / SC285 Functions & Specifications

Specialty toners are available in “Revoria Press SC285S” or “Revoria Press SC285 equipped with the specialty toner option”. Specialty toners can be used in addition to CMYK for overprinting.

Basic Specifications

| Item | | Description |
|---------------------------|--------------------------|--|
| Color capability | | Full color |
| Print resolution | | 2,400 x 2,400 dpi |
| Warm-up time | | 300 seconds or less (room temperature 23°C) |
| Continuous print speed*1 | | A4: 85 ppm, A3: 47 ppm |
| Paper size*2 | Tray 1, 2, 3 | 140 x 182 mm to 330 x 488 mm |
| | Bypass tray (Optional)*3 | 90 x 146 mm to 330 x 1,300 mm*4 |
| Paper weight | Tray 1, 2, 3 | 64 to 256 gsm |
| | Bypass tray (Optional)*3 | 52 to 300 gsm*5 |
| Paper capacity*6 | Tray 1, 2, 3 | 570 sheets x 3-tray |
| | Bypass tray (Optional)*3 | 250 sheets |
| Power supply | | Single-phase AC200-240 V +/-10%, 20 A, 50/60 Hz, ground connection |
| Maximum power consumption | | 4.8 kW (in case of 240 V) |
| Dimensions*7 | | W 1,159 x D 858 x H 1,310 mm |
| Weight*8 | | 288 kg or less (include bypass tray) 282 kg or less (exclude bypass tray) |

*1: When continuously printing a single sided document. 52 to 350 gsm, uncoated paper. Print speed may be reduced depending on conditions of output data, on whether specialty toner is used, on whether auto image quality adjustment is performed, on whether the job includes a mixture of paper sizes and types, and other reasons.

*2: Image loss width: lead edge 4.0 mm, trail edge 2.0 mm, front 2.0 mm, rear 2.0 mm.

*3: When the optional bypass tray (Multi Sheet Inserter for Banner Print) is directly connected to the printer unit.

*4: Up to 330 x 660 mm paper is supported in duplex automatic printing. To use paper longer than 488 mm, feed and output options compatible with that paper size are required.

*5: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*6: 82 gsm paper.

*7: Printer unit + Bypass tray (Multi Sheet Inserter for Banner Print). Excludes feeding / output options. Bypass tray is closed.

*8: Printer unit + Bypass tray (Multi Sheet Inserter for Banner Print). Excludes feeding / output options. Excludes toner cartridges. When connecting the paper feed option, please be aware that the weight of the bypass tray may be included in the feed option.

Internal Print Function

| Item | Description |
|---------------------------------|--|
| Continuous print speed | [PCL Driver] Same as the Basic Specifications |
| Paper size | [PCL Driver] Same as the Basic Specifications |
| Data resolution | [PCL Driver] Standard: 2,400 x 2,400 dpi, High Resolution: 2,400 x 2,400 dpi |
| PDL (Page Description Language) | PCL |
| Printer driver OS ^{*1} | [PCL Driver] Windows 11 (64bit), Windows 10 (32bit / 64bit), Windows Server 2022 (64bit), Windows Server 2019 (64bit), Windows Server 2016 (64bit) |
| Connecting port | Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T, USB2.0 |

*1: Please refer to our official website for the latest supported OS.

Scan Function

| Item | Description |
|-----------------|---|
| Type | Color scanner |
| Document size | [Document glass / Duplex Automatic Document Feeder] Standard size: Max A3, 11 × 17", Min A6, 5.5 × 8.5" Custom size: 15 × 15 mm to 297 × 432 mm |
| Scan resolution | 600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi |
| Scan speed | Same as the "Scan speed" of the Duplex Automatic Document Feeder |
| Scan output | Store to folder (TWAIN interface support), Scan to PC, Scan to e-mail |

Copy Function

| Item | Description |
|--------------------------------------|---|
| Document size | [Document glass / Duplex Automatic Document Feeder] Standard size: Max A3, 11 × 17", Min A6, 5.5 × 8.5" Custom size: 15 × 15 mm to 297 × 432 mm |
| Paper size ^{*1} | Standard size: Max A3, 11 × 17", Min A6, 5.5 × 8.5" Custom size: 90 x 146 mm to 330 x 1,300 mm ^{*2} |
| Scan resolution | 600 x 600 dpi |
| Print resolution | 2,400 x 2,400 dpi (Text-Photo / Photo), 600 x 600 dpi (Text / Map) |
| Tone | 256 levels of each color |
| First copy output time ^{*3} | B/W: 5.2 sec. or less (A4 / Monochrome priority mode) Color: 9.0 sec. or less (A4 / Color priority mode) |

*1: Image loss width: Lead edge 4.0 mm, Trail edge 2.0 mm, Front 2.0 mm, Rear 2.0 mm.

*2: To use paper longer than 488 mm, feed and output options compatible with that paper size are required.

*3: When the original is placed on the document glass, paper is fed from tray 1, the document is copied from simplex-to-simplex output and a copy is output to the Offset Catch Tray.

Duplex Automatic Document Feeder

| Item | | Description |
|-----------------------|------|--|
| Document size | | Please refer Scan function and Copy function. |
| Document paper weight | | 38 to 200 gsm (In Duplex: 50 to 200 gsm) |
| Document capacity*1 | | 250 sheets |
| Scan speed*2 | Copy | B/W: 90 ppm, Color: 90 ppm (A4 LEF, 1-sided) |
| | Scan | 1-sided scanning: 135 ppm, 2-sided scanning: 270 ppm [Standard document (A4), 200 dpi, store to folder] |

*1 80 gsm paper.

*2 The scanning speed varies depending on the documents.

Print Server [Revoria Flow SC21 / SC22]

| Item | Description | |
|---------------------------|--|---|
| | Revoria Flow SC21 | Revoria Flow SC22 *1 |
| Type | External | |
| CPU | Intel® Xeon® E-2226GE Processor (3.4- 4.6 GHz) | Intel® Core™ i3-9100E Processor (3.1-3.7 GHz) |
| Memory | 32 GB (Max 32 GB) | 16 GB (Max 32 GB, Optional) |
| Storage device | Hard disk: 4 TB (System), SSD: 1,920 GB, DVD Multi drive | Hard disk: 1 TB (System), SSD (optional): 1,920 GB, DVD Multi Drive |
| Server OS | Windows 10 IoT Enterprise LTSC 2021 (64bit) | |
| Print data format | PS, PDF2.0, PDF/X-1a, PDF/X-3, PDF/X-4, PDF/X-5, EPS, TIFF, JPEG, PDF/VT, PPML | |
| RIP type | Adobe® PostScript® 3™ (Configurable PostScript Interpreter), Adobe® PDF Print Engine 6 | Adobe® PostScript® 3™ (Configurable PostScript Interpreter), Adobe® PDF Print Engine 6 (Optional) |
| Printer driver OS*2 | Windows 11 (64bit), Windows 10 (32bit / 64bit), Windows Server 2025 (64bit), Windows Server 2022 (64bit), Windows Server 2019 (64bit), Windows Server 2016 (64bit), macOS 15 / 14 / 13 / 12 / 11 | |
| Connecting port | Ethernet 1000BASE-T / 100BASE-TX / 10BASE-T x 2 | |
| Network protocol | LPR, FTP, SMB, HTTP, JDF, SNMP, Bonjour | |
| Power supply | Single-phase AC100-240 V +/- 10%, 3.6 A (100 V) / 1.5 A (240 V), 50/60 Hz, ground connection | |
| Maximum power consumption | 0.4 kW (in case of 240 V) | |
| Dimensions*3 | W 170 x D 403x H 358 mm | |
| Weight*3 | 8.9 kg or less | |

*1 Optional memory is required for duplex printing longer than 660 mm paper. Optional memory is required for printing longer than 660 mm paper at 1,200 x 1,200 dpi.

*2: Please refer to our official website for the latest supported OS.

*3: Print Server only. Excludes monitor, mouse, and keyboard.

High Capacity Feeder B1 (Optional)

| Item | Description |
|------------------------------|--|
| Paper size | Max A4, Letter, Min JIS B5, 7.25 x 10.5" |
| Paper weight | 64 to 220 gsm |
| Paper capacity ^{*1} | 2,100 sheets x 1-tray |
| Dimensions | W 389 x D 610 x H 377 mm |
| Weight ^{*2} | 29 kg or less |

Note: Optional bypass tray (Multi Sheet Inserter for Banner Print) is required. It is connected to the printer directly.

*1 82 gsm paper.

*2 Excludes bypass tray (Multi Sheet Inserter for Banner Print).

High Capacity Feeder B1-S / High Capacity Feeder C3-DS / 2nd High Capacity Feeder C1-DS (Optional)

| Item | | Description | | |
|------------------------------|----------------------------------|---|---|---|
| | | High Capacity Feeder B1-S | High Capacity Feeder C3-DS | 2nd High Capacity Feeder C1-DS |
| Paper size | High-capacity tray ^{*1} | Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", JIS B5 Custom size: 98 x 148 mm to 330 x 488 mm | Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", JIS B5 Custom size: 98 x 148 mm to 330 x 488 mm | Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", JIS B5 Custom size: 98 x 148 mm to 330 x 488 mm |
| | Bypass tray (Optional) | Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm | Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm | - |
| Paper weight | High-capacity tray | 52 to 300 gsm | 52 to 350 gsm | 52 to 350 gsm |
| | Bypass tray (Optional) | 52 to 350 gsm ^{*2} | 52 to 350 gsm ^{*2} | - |
| Paper capacity ^{*3} | High-capacity tray | 2,100 sheets x 1-tray | 2,100 sheets x 2-tray | 2,100 sheets x 2-tray |
| | Bypass tray (Optional) | 250 sheets | 250 sheets | - |
| Power supply | | Single-phase AC100-120 V +/- 10%, 2.5 A / AC220-240 V +/- 10%, 1.5 A, 50/60 Hz, ground connection | Single-phase AC100-120 V +/- 10%, 6 A / AC200-240 V +/- 10% 4 A, 50/60 Hz, ground connection | Single-phase AC100-120 V +/- 10%, 6 A / AC200-240 V +/- 10%, 4 A, 50/60 Hz, ground connection |
| Maximum power consumption | | 360 W (in case of 240 V) | 880 W (in case of 240 V) | 880 W (in case of 240 V) |
| Dimensions ^{*4} | | W 988 x D 762 x H 992 mm | W 988 x D 762 x H 992 mm | W 988 x D 762 x H 992 mm |
| Weight | | 177 kg or less ^{*4} | 232 kg or less ^{*4} | 235 kg or less |

Note: Optional bypass tray (Multi Sheet Inserter for Banner Print) is required for the High Capacity Feeder B1-S or High Capacity Feeder C3-DS.

Note: When connecting the High Capacity Feeder C3-DS and 2nd High Capacity Feeder C1-DS, the optional bypass tray (Multi Sheet Inserter for Banner Print) is attached to the left module.

*1: Post Card Kit is required to use paper with a width of less than 182 mm.

*2: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*3: 82 gsm paper.

*4: Including optional bypass tray (Multi Sheet Inserter for Banner Print).

Air Suction Feeder C1-DS / Chained Air Suction Feeder C1-DS (Optional)

| Item | | Description | |
|------------------------------|----------------------------------|---|--|
| | | Air Suction Feeder C1-DS | Chained Air Suction Feeder C1-DS-R + Chained Air Suction Feeder C1-DS-L |
| Paper size | High-capacity tray ^{*1} | Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", A5 Custom size: 98 x 148 mm to 330 x 488 mm | Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", A5 Custom size: 98 x 148 mm to 330 x 488 mm |
| | Bypass tray | Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm | Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm |
| Paper weight | High-capacity tray | 52 to 400 gsm | 52 to 400 gsm |
| | Bypass tray | 52 to 350 gsm ^{*2} | 52 to 350 gsm ^{*2} |
| Paper capacity ^{*3} | High-capacity tray | 2,200 sheets x 2-tray | 2,200 sheets x 2-tray x 2-connection |
| | Bypass tray | 250 sheets | 250 sheets |
| Power supply | | Single-phase AC100-120 V +/- 10%, 6 A / AC200-240 V +/- 10%, 4 A, 50/60 Hz, ground connection | Single-phase AC100-120 V +/- 10 %, 6 A / AC200-240 V +/- 10 %, 4 A, 50/60 Hz, ground connection Single-phase AC100-120 V +/- 10 %, 6 A / AC200-240 V +/- 10 %, 4 A, 50/60 Hz, ground connection |
| Maximum power consumption | | 880 W (in case of 240 V) | 880 W + 880 W (in case of 240 V) |
| Dimensions | | W 988 x D 762 x H 992 mm | W 1,980 x D 762 x H 992 mm |
| Weight | | 194 kg or less | 403 kg or less |

Note: Bypass tray (Multi Sheet Inserter for Banner Print) is included.

*1: Post Card Kit for Air Suction Feeder is required to use paper with a width of less than 182 mm.

*2: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*3: 82 gsm paper.

Air Suction Feeder C1-DSXL / Chained Air Suction Feeder C1-DSXL (Optional)

| Item | | Description | |
|------------------------------|--------------------|--|--|
| | | Air Suction Feeder C1-DSXL + Banner Unit for Air Suction Feeder C1-DSXL | Chained Air Suction Feeder C1-DS-R + Chained Air Suction Feeder C1-DSXL-L + Banner Unit for Air Suction Feeder C1-DSXL |
| Paper size ^{*1} | High-capacity tray | [Upper tray] Standard size: Max 13 x 19", SRA3, A3, Min A4, Letter Custom size: 210 x 210 mm to 330 x 1,300 mm ² [Lower tray] Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", A5 Custom size: 98 x 148 mm to 330 x 488 mm | [Upper tray of the left module] Standard size: Max 13 x 19", SRA3, A3, Min A4, Letter Custom size: 210 x 210 mm to 330 x 1,300 mm ² [Lower tray of the left module, upper and lower tray of the right module] Standard size: Max 13 x 19", SRA3, A3, Min 4 x 6", A5 Custom size: 98 x 148 mm to 330 x 488 mm |
| | Bypass tray | Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm | Standard size: Max 13 x 19", SRA3, A3, Min A6, 5.5 x 8.5" Custom size: 90 x 146 mm to 330 x 660 mm |
| Paper weight | High-capacity tray | 52 to 400 gsm ^{*3} | 52 to 400 gsm ^{*3} |
| | Bypass tray | 52 to 350 gsm ^{*4} | 52 to 350 gsm ^{*4} |
| Paper capacity ^{*5} | High-capacity tray | 900 sheets ^{*6} + 2,200 sheets | 2,200 sheets x 2-tray + 900 sheets ^{*6} + 2,200 sheets |
| | Bypass tray | 250 sheets | 250 sheets |
| Power supply | | Single-phase AC100-120 V +/- 10%, 6 A / AC200-240 V +/- 10%, 4 A, 50/60 Hz, ground connection | Single-phase AC100-120 V +/- 10 %, 6 A / AC200-240 V +/- 10 %, 4 A, 50/60 Hz, ground connection Single-phase AC100-120 V +/- 10 %, 6 A / AC200-240 V +/- 10 %, 4 A, 50/60 Hz, ground connection |
| Maximum power consumption | | 880 W (in case of 240 V) | 880 W + 880 W (in case of 240 V) |
| Dimensions | | W 1,580 x D 762 x H 992 mm | W 2,572 x D 762 x H 992 mm |
| Weight | | 213 kg or less | 420 kg or less |

Note: Bypass tray (Multi Sheet Inserter for Banner Print) is included.

Note: Air Suction Feeder C1-DSXL can feed long sheet only from the Upper tray.

Note: Chained Air Suction Feeder C1-DSXL-L can feed long sheet only from the Upper tray.

*1: Post Card Kit for Air Suction Feeder is required to use paper with a width of less than 182 mm.

*2: Up to 330 x 864 mm paper is supported in duplex automatic printing.

*3: Paper length 488+ to 660 mm: 52 to 350 gsm, 660+ to 864 mm: 52 to 300 gsm, 864+ to 1,200 mm: 52 to 256 gsm. 1,200+ to 1,300 mm can only be used for certain brands of 104 gsm. Duplex automatic printing supports paper weight up to 300 gsm.

*4: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*5: 82 gsm paper.

*6: Up to 100 sheets (82 gsm) of paper longer than 864 mm can be used.

Offset Catch Tray / Long Catch Tray (Optional)

| Item | Description | |
|-----------------------------|---|---|
| | Offset Catch Tray | Long Catch Tray |
| Paper size | 90 x 146 mm to 330 x 660 mm ^{*1} | 90 x 146 mm to 330 x 1,300 mm ^{*2} |
| Paper weight | 52 to 400 gsm | 52 to 400 gsm |
| Tray capacity ^{*3} | 500 sheets | 300 sheets (Paper length up to 488 mm) 100 sheets (Paper length above 488 to 864 mm) 10 sheets (Paper length above 864 to 1,300 mm) |
| Dimensions | W 406 x D 393 x H 184 mm | W 512 x D 396 x H 308 mm ^{*4} |
| Weight | 6 kg or less | 4 kg or less ^{*5} |

Note: Catch Tray Fan Kit (optional) are required.

*1: Tray capacity is not guaranteed larger than 330 x 488 mm sheet.

*2: Up to 330 x 660 mm sheet can be accommodated when Long Paper Extension Kit is not installed.

*3: 82 gsm paper.

*4: When Long Paper Extension Kit is installed, W 941 x D 396 x H 495 mm.

*5: When Long Paper Extension Kit is installed, 5 kg or less.

Folder Unit CD3 (Optional)

| Item | | Description |
|---------------------------|----------------------------|---|
| Z fold half sheet | Paper size | A3, 11 x 17", JIS B4 |
| | Paper weight | 60 to 90 gsm |
| Trifold | Paper size | A4, Letter |
| | Paper weight | 60 to 90 gsm |
| | Tray capacity [*] | 30 sheets |
| Power supply | | Single-phase AC100-240 V +/- 10 %, 1 A (100 V) / 0.5 A (240 V), 50/60 Hz, ground connection |
| Maximum power consumption | | 120 W (in case of 240 V) |
| Dimensions | | W 232 x D 588 x H 992 mm |
| Weight | | 52 kg or less |

Note: Folder Unit CD3 is an option for Finisher-C5 and Finisher-C5 with Booklet Maker.

*1: 82 gsm paper.

Finisher-C5 / Finisher-C5 with Booklet Maker (Optional)

| Item | | Description | |
|-----------------------------|---|---|---|
| | | Finisher-C5 + Transport Unit v2 | Finisher-C5 with Booklet Maker + Transport Unit v2 |
| Type | Output tray | Sort (Offset available) / Stack (Offset available) | |
| | Finishing tray | Sort (Offset available) / Stack (Offset available) | |
| | Booklet tray | - | Sort / Stack |
| Paper size ^{*1} | Output tray | 90 x 146 mm ^{*2} to 330 x 1,300 mm ^{*3} | |
| | Finishing tray | 203 x 148 mm to 330 x 488 mm | |
| Paper weight ^{*1} | Output tray | 52 to 350 gsm ^{*4,5} | |
| | Finishing tray | 52 to 350 gsm ^{*5} | |
| Tray capacity ^{*6} | Output tray | 500 sheets (A4) ^{*3} | |
| | Finishing tray | [Without stapling] A4: 3,000 sheets JIS B4 or larger: 1,500 sheets A5: 1,000 sheets Mixed size stacking ^{*7} : 300 sheets [With stapling] A4: 200 sets (Single stapling), 100 sets (Dual stapling) or 3,000 sheets JIS B4 or larger: 100 sets or 1,500 sheets A5: 100 sets or 1,000 sheets (Single stapling), 75 sets or 750 sheets (Dual stapling) Mixed size stacking ^{*7} : 70 sets or 200 sheets | [Without stapling] A4: 1,500 sheets JIS B4 or larger: 1,500 sheets A5: 1,000 sheets Mixed size stacking ^{*7} : 300 sheets [With stapling] A4: 200 sets (Single stapling), 100 sets (Dual stapling) or 1,500 sheets JIS B4 or larger: 100 sets or 1,500 sheets A5: 100 sets or 1,000 sheets (Single stapling), 75 sets or 750 sheets (Dual stapling) Mixed size stacking ^{*7} : 70 sets or 200 sheets |
| | Booklet tray | - | 20 sets ^{*8} |
| Staple | Staple capacity | Staple: Max 50 sheets (90 gsm or less) ^{*9} Staple-free staple ^{*10} : Max 10 sheets (80 gsm or less) | |
| | Paper size ^{*11} | [Single stapling, Dual stapling / Staple-free stapling ^{*10}] Standard size: Max A3, 11 x 17", Min A5, 6 x 9" Custom size: 203 x 148 mm to 297 x 432 mm [4 stapling] Standard size: A4, Letter | |
| | Paper weight | Staple: 52 to 350 gsm Staple-free staple ^{*10} : 60 to 105 gsm | |
| | Staple position | Single stapling, Dual stapling, 4 stapling | |
| Punch ^{*12} | Number of holes | 2-hole / 4-hole punch or 2-hole / 3-hole punch (US specifications) | |
| | Paper size ^{*13} | Standard size: 2-hole punch Max A3, 11 x 17", Min A5, 7.25 x 10.5" 3-hole punch Max A3, 11 x 17", Min JIS B5, 7.25 x 10.5" 4-hole punch Max A3, 11 x 17", Min A4, 7.25 x 10.5" Custom size: 2-hole punch 203 x 148 mm to 297 x 432 mm 3-hole punch 254 x 148 mm to 297 x 432 mm 4-hole punch 267 x 148 mm to 297 x 432 mm | |
| | Paper weight | 52 to 220 gsm | |
| Booklet finishing | Booklet finishing capacity ^{*14} | - | Saddle staple: 20 sheets (90 gsm or less) Single fold: 5 sheets (90 gsm or less) |
| | Paper size | - | Standard size: Max 13 x 18", SRA3, A3, Min JIS B5, 7.25 x 10.5" Custom size: 182 x 257 mm to 330 x 457 mm |
| | Paper weight | - | Saddle staple: 60 to 300 gsm Single fold: 60 to 300 gsm |
| Dimensions ^{*15} | W 771 x D 692 x H 1,054 mm | | W 776 x D 692 x H 1,054 mm |
| Weight | 53 kg or less | | 65 kg or less |

*1: Without stapling, punching or booklet finishing.

*2: When using 90x146mm, please check the print run in advance.

*3: Tray capacity is not guaranteed larger than 330 x 488 mm sheet.

*4: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*5: 52 to 220 gsm paper may not be aligned properly depending on the paper type.

*6: 82 gsm paper.

*7: When larger size sheets are stacked on top of smaller size sheets.

*8: When printing on the same size of paper.

*9: Up to 65 sheets can be stapled when the optional Finisher-C Staple Unit 65 Sheets is installed. However incorrect stapling such as uneven edge alignment may occur depending on the paper type.

*10: Staple-free stapling does not have binding force equal to stapled stapling. Bound part may be easily separated depending on the paper type, temperature, humidity, and how the page is turned over.

*11: Staple positions available depends on the paper size.

*12: Punching function is provided as standard.

*13: The number of punch holes available depends on the paper size.

*14: The number of sheets that can be booklet finished varies depending on the paper weight. Booklet may not be tightly closed depending on the size or type of the paper.

*15: When the extension tray is pulled out.

Interface Decurler Module D1 (Optional)

| Item | Description |
|---------------------------|---|
| Power supply | Single-phase AC100-240 V +/- 10 %, 2.5 A (100 V) / 1 A (240 V), 50/60 Hz, ground connection |
| Maximum power consumption | 250 W (in case of 240 V) |
| Dimensions | W 340 x D 725 x H 992 mm |
| Weight | 40 kg or less |

Note: Interface Decurler Module D1 is necessary for connecting High Capacity Stacker A2, High Capacity Stacker A2 with Transport Module, Finisher D6, or Finisher D6 with Booklet Maker to the printer.

Inserter D1 (Optional)

| Item | Description |
|-------------------|--|
| Paper size | Standard size: Max 12.6 x 19.2", SRA3, A3, Min A5, 6 x 9" Custom size: 182 x 148 mm to 330 x 488 mm |
| Paper weight | 52 to 350 gsm |
| Paper capacity *1 | 250 sheets |
| Power supply | Supplied from Interface Decurler Module D1 |
| Dimensions | W 700*2 x D 725 x H 1,235 mm |
| Weight | 45 kg or less |

Note: High Capacity Stacker A2, High Capacity Stacker A2 with Transport Module, Finisher D6, or Finisher D6 with Booklet Maker is required.

*1: 82 gsm paper.

*2: The width of only the paper transfer part is 165 mm.

Static Eliminator D1 (Optional)

| Item | Description |
|---------------------------|---|
| Power supply | Single-phase AC100-240 V +/- 10 %, 0.6 A (100 V) / 0.3 A (240 V), 50/60 Hz, ground connection |
| Maximum power consumption | 72 W (in case of 240 V) |
| Dimensions | W 232 x D 725 x H 992 mm |
| Weight | 40 kg or less |

Note: High Capacity Stacker A2, High Capacity Stacker A2 with Transport Module, Finisher D6 or Finisher D6 with Booklet Maker is required.

Smart Monitoring Gate D1 (Optional)

| Item | Description |
|---------------------------|---|
| Power supply | Single-phase AC100-240 V +/- 10 %, 2.4 A (100 V) / 1.2 A (240 V), 50/60 Hz, ground connection |
| Maximum power consumption | 240 W (in case of 240 V) |
| Dimensions | W 605 x D 725 x H 992 mm |
| Weight | 92 kg or less |

Note: High Capacity Stacker A2, High Capacity Stacker A2 with Transport Module, Finisher D6 or Finisher D6 with Booklet Maker is required.

High Capacity Stacker A2 / High Capacity Stacker A2 with Transport Module (Optional)

| Item | | Description | |
|---------------------------|--------------|---|--|
| | | High Capacity Stacker A2 | High Capacity Stacker A2 with Transport Module |
| Tray capacity*1 | Output tray | 500 sheets*2 | |
| | Stacker cart | 5,000 sheets or stacking height is less than 570 mm. | |
| Paper size | Output tray | 90 x 146 mm*3 to 330 x 1,300 mm*2 | |
| | Stacker cart | 203 x 182 mm to 330 x 488 mm | |
| Paper weight | Output tray | 52 to 400 gsm*4 | |
| | Stacker cart | 52 to 300 gsm | |
| Power supply | | Single-phase AC100-240 V +/- 10 %, 1.5 A (100 V) / 0.8 A (240 V), 50/60 Hz, ground connection | |
| Maximum power consumption | | 192 W (in case of 240 V) | |
| Dimensions | | W 800 x D 725 x H 1,042 mm | W 848 x D 725 x H 1,042 mm |
| Weight*5 | | 155 kg or less | 159 kg or less |

Note: Interface Decurler Module D1 is required.

Note: High Capacity Stacker A2 with Transport Module is an option for connecting a third party vendor finisher. For a third party vendor finisher, please contact your local FUJIFILM Business Innovation representative.

*1: 82 gsm paper.

*2: Tray capacity is not guaranteed larger than 330 x 488 mm sheet. When the optional Banner Print Extension Kit is installed, 250 sheets of up to 330 x 488 mm, 100 sheets of up to 330 x 864 mm, 10 sheets of up to 330 x 1,300 mm paper can be accommodated.

*3: When using 90 x 146mm, please check the print run in advance.

*4: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*5: Including a Stacker Cart.

Crease/Two-sided Trimmer D2 (Optional)

| Item | | Description |
|---------------------------|---|------------------------------|
| Two-sided trim | Paper size | 194 x 210 mm to 330 x 488 mm |
| | Paper weight | 52 to 350 gsm |
| | Trim dimensions | One side: 6 to 25 mm |
| Crease | Paper size | 182 x 210 mm to 330 x 488 mm |
| | Paper weight ^{*1} | 60 to 350 gsm |
| | Number of crease lines ^{*2} | 1 to 5 |
| Power supply | Single-phase AC100-240 V +/- 10 %, 4.0 A (100 V) / 2.0 A (240 V), 50/60 Hz, ground connection | |
| Maximum power consumption | 480 W (in case of 240 V) | |
| Dimensions | W 605 x D 725 x H 992 mm | |
| Weight | 128 kg or less | |

Note: Finisher D6 or Finisher D6 with Booklet Maker is required.

*1: When creasing with booklet finishing. In case of creasing a single sheet without folding, 157 gsm or more paper can be used.

*2: The continuous print speed will decrease significantly as the number of creasing lines increases.

Folder Unit CD2 (Optional)

| Item | | Description |
|---------------------------|---|----------------------|
| Z Fold half sheet | Paper size | A3, 11 x 17", JIS B4 |
| | Paper weight | 60 to 90 gsm |
| Trifold | Paper size | A4, Letter |
| | Paper weight | 60 to 90 gsm |
| | Tray capacity ^{*1} | 30 sheets |
| Power supply | Single-phase AC100-240 V +/- 10 %, 1 A (100 V) / 0.5 A (240 V), 50/60 Hz, ground connection | |
| Maximum power consumption | 120 W (in case of 240 V) | |
| Dimensions | W 232 x D 725 x H 992 mm | |
| Weight | 55 kg or less | |

Note: Folder Unit CD2 is an option for Finisher D6 and Finisher D6 with Booklet Maker.

*1: 82 gsm paper.

Finisher D6 / Finisher D6 with Booklet Maker (Optional)

| Item | | Description | |
|-----------------------------|---|--|---|
| | | Finisher D6 | Finisher D6 with Booklet Maker |
| Type | Output tray | Sort / Stack | |
| | Finishing tray | Sort (Offset available) / Stack (Offset available) | |
| | Booklet tray | - | Sort / Stack |
| Paper size* ¹ | Output tray | 90 x 146 mm ² to 330 x 1,300 mm ³ | |
| | Finishing tray | 148 x 146 mm to 330 x 488 mm | |
| Paper weight* ¹ | Output tray | 52 to 400 gsm ⁴ | |
| | Finishing tray | 52 to 350 gsm | |
| Tray capacity* ⁵ | Output tray | 500 sheets (A4) | |
| | Finishing tray | [Without stapling] A4: 3,000 sheets JIS B4 or larger: 1,500 sheets Mixed size stacking* ⁶ : 350 sheets [With stapling] A4: 200 sets or 3,000 sheets JIS B4 or larger: 100 sets or 1,500 sheets | [Without stapling] A4: 2,000 sheets JIS B4 or larger: 1,500 sheets Mixed size stacking* ⁶ : 350 sheets [With stapling] A4: 200 sets or 2,000 sheets JIS B4 or larger: 100 sets or 1,500 sheets |
| | Booklet tray | - | 20 sets (16 sheets/set or less) ⁷ |
| Staple | Staple capacity | Max 100 sheets (90 gsm or less) ⁸ | |
| | Paper size* ⁹ | Standard size: Max A3, 11 x 17", Min A5, 8 x 10" Custom size: 182 x 146 mm to 297 x 432 mm | |
| | Paper weight | 52 to 350 gsm | |
| | Staple position | Single stapling, Dual stapling, 4 stapling | |
| Punch* ¹⁰ | Number of holes | 2-hole / 4-hole punch or 2-hole / 3-hole punch (US Specifications) | |
| | Paper size* ¹¹ | Standard size: 2-hole punch Max A3, 11 x 17", Min JIS B5, 8 x 10" 3-hole punch Max A3, 11 x 17", Min JIS B5, 8 x 10" 4-hole punch Max A3, 11 x 17", Min A4, Letter Custom size: 2-hole punch 203 x 182 mm to 297 x 432 mm 3-hole punch 254 x 182 mm to 297 x 432 mm 4-hole punch 267 x 182 mm to 297 x 432 mm | |
| | Paper weight | 52 to 220 gsm | |
| Booklet finishing | Booklet finishing capacity* ¹² | - | Saddle staple: Max 30 sheets (90 gsm or less) Single fold: Max 5 sheets (220 gsm or less) |
| | Paper size | - | Standard size: Max 13 x 19", SRA3, A3, Min JIS B5, 7.25 x 10.5" Custom size: 182 x 257 mm to 330 x 488 mm |
| | Paper weight | - | 60 to 350 gsm |
| Power supply | Single-phase AC100-240 V +/- 10 %, 3.0 A (100 V) / 1.5 A (240 V), 50/60 Hz, ground connection | | |
| Maximum power consumption | 360 W (in case of 240 V) | | |
| Dimensions | W 855 x D 725 x H 1,204 mm | W 892 x D 725 x H 1,204 mm | |
| Weight | 87 kg or less | 107 kg or less | |

Note: Interface Decurler Module D1 is required.

*1: Without stapling, punching or booklet finishing.

*2: When using 90x146mm, please check the print run in advance.

*3: Tray capacity is not guaranteed larger than 330 x 488 mm sheet. When the optional Banner Print Extension Kit is installed, 150 sheets of up to 330 x 660 mm, 100 sheets of up to 330 x 864 mm, 10 sheets of up to 330 x 1,300 mm paper can be accommodated.

*4: Sheets longer than 488 mm can be used with weights from 52 to 220 gsm.

*5: 82 gsm paper.

*6: When larger size sheets are stacked on top of smaller size sheets.

*7: Booklet tray capacity is 16 sets (17-20 sheets/set), 12 sets (21-25 sheets/set) and 10 sets (26-30 sheets/set).

*8: Up to 65 sheets can be stapled for paper sizes exceeding A4 or letter.

*9: Staple positions available depends on the paper size.

*10: Optional.

*11: The number of punch holes available depends on the paper size.

*12: The number of sheets that can be booklet finished varies depending on the paper weight. Booklet may not be tightly closed depending on the size or type of the paper.

Square Back Fold Trimmer D1 (Optional)

| Item | | Description |
|--------------------------------|----------------------|---|
| Paper size | | Same as the “paper size” of the Finisher D6 Booklet Finishing. |
| Paper weight | | Same as the “paper weight” of the Finisher D6 Booklet Finishing. |
| Booklet tray capacity*1 | | Max 20 sets (16 sheets/set or less)*2 |
| Face trim | Face trim capacity*3 | Saddle staple: Max 30 sheets, Single fold: Max 5 sheets |
| | Face trim dimensions | 2 to 20 mm |
| Square back fold capacity*3 *4 | | Max 30 sheets |
| Power supply | | Single-phase AC100-240 V +/- 10 %, 1.0 A (100 V) / 0.6 A (240 V), 50/60 Hz, ground connection |
| Maximum power consumption | | 144 W (in case of 240 V) |
| Dimensions | | W 1,066 x D 725 x H 552 mm |
| Weight | | 100 kg or less |

Note: Finisher D6 with Booklet Maker is required.

*1: Paper may not be accepted depending on paper type and other usage conditions.

*2: Booklet tray capacity is 16 sets (17-20 sheets/set), 12 sets (21-25 sheets/set) and 10 sets (26-30 sheets/set).

*3: The capacity can decrease depending on type and weight of paper being used and other conditions.

*4: Square back folding does not support single-folded sheets and less than 5 sheets of saddle-stapled paper.

Notes

- Performance is not guaranteed for all paper types. Please contact your local FUJIFILM Business Innovation representative for recommended paper.
- Functional spare parts will be available for at least 7 years after the product is no longer manufactured.

fujifilm.com/fb

FUJIFILM

FUJIFILM Business Innovation Corp.

7-3, Akasaka 9-Chome, Minato-ku Tokyo 107-0052, Japan

Trademarks •FUJIFILM and FUJIFILM logo are registered trademarks or trademarks of FUJIFILM Corporation. •Revorvia, Revorvia logo, Revorvia Press and Revorvia Flow are registered trademark or trademark of FUJIFILM Business Innovation Corp. •Adobe, Adobe logo, PostScript and PostScript logo, Adobe PDF, Adobe PDF Print Engine are either registered trademarks or trademarks of Adobe in the United States and/or other countries. •All product names and company names mentioned in this brochure are trademarks or registered trademarks of their respective companies.

The information is as of April 2026